

Standard Features

Anti Restart Ignition Switch
 Dual Rear Brakes No Front Brakes
 E-Type Hitch on Rear
 Forward, Neutral, Reverse Shifter
 Gauges: WaterTemp./Oil Pressure/
 Volt Meter/Hour Meter/Fuel
 Leaf Springs on Front & Rear Axles
 Manual Park Brake
 Manual Steering
 Non-Slip Surface Flooring
 One Stop/Tail Light
 One Backup Light
 Power Split Braking System
 Standard Color: White
 Two Headlights



HTA30 HTA40 HTA50 HTA60 HTA70 HTA80

Tractors with 3,000 to 8,000 lb. Drawbar Pull

ENGINE

TRANSMISSION

HORSEPOWER (Kw)

TORQUE FT-LBS. (N-m)

Ford ESG 6-4.2

Ford C-6 Automatic
 107hp (75 kW)
 203 ft. lbs. (263 N-m)

Cummins 4B3.9C

Ford C-6 Automatic
 76 (56.7 kW)
 184 ft. lbs. (250 N-m)

Perkins 1004-4

Ford C-6 Automatic
 86 (64 kW)
 206 ft. lbs. (279 N-m)

Battery

12 Volt

Cooling System

Liquid cooled 10 quart capacity radiator with integral transmission cooler

Tires

6.50 x 10 Tubeless (front)
 7.50 x 16 Tubeless (rear)

Overall Dimensions

	Single Drive	Dual Drive
Length	102" (2591mm)	112" (2844mm)
Width	55.5" (1410mm)	65.5" (1663mm)
Height	63" (1600mm)	63" (1600mm)
(w/Cab)	86.25" (2191mm)	86.25" (2191mm)

Turning Radius

	Single Drive	Dual Drive
Intersecting Aisle	120" (3048mm)	135" (3429mm)
	90" (2286mm)	97" (2463mm)

Top Speeds

No Load
 16mph (25.7 km/h)
Load
 14mph (22.5 km/h)

Max. Drawbar

3,000-4,000-5,000-6,000-7,000-
 8,000lb. Drawbar Pull
 (13.3 to 35.5 kN)

Service Weight

Depends on model designation
 4,500, 5,000, 6,250, 7,500,
 8,900, 9,900 lbs.
 (2519 to 4490 kg)

Wheel Base

Single 58" (1473mm)
Dual 68" (1727mm)

Ground Clearance

6" (152mm)

Brake Options

Hydraulic/Vacuum Assist or
 Hydraulic over Hydraulic
 Mechanical Drum Parking Brake
 Front Drum, Rear Single Caliper Disc
 4 Wheel Drive Brakes

Steering Options

Manual, Power Steering

Axles

Steer Axle Harlan 1 1/8" King Pin
 Drive Axle Harlan 10,000 lb. Capacity
 (check option list for different ratios)

Towing Coupler

Customer Option

Specifications subject to improvement and / or change without notice.

revised: 8/3/00

HARLAN CORPORATION
 27 Stanley Road Kansas City, Kansas 66115 U.S.A.
 Toll Free:1-800-255-4262 Phone:1-913-342-5650
 Fax:1-913-321-5802 Website:www.harlan-corp.com

HTA 30-80



VICTORY GROUND SUPPORT EQUIPMENT
 (323) 581-7272 www.victorygse.com